

**BY ORDER OF THE
SECRETARY OF THE AIR FORCE**

**AFI 11-2C-5V3, CL-5
1 JANUARY 2000**



Flying Operations

C-5 Special Operations (SOLL II)

This checklist establishes procedures for the operation of C-5 aircraft employed by Mobility Air Forces (MAF) to accomplish their worldwide missions. It does not apply to Air National Guard and US Air Force Reserve units.

This checklist complements AFI 11-2C-5V3, *C-5 Operations Procedures*, and is printed on standard 8 ½” x 11” bond paper then trimmed to a unique size 4 ½ “ x 6 ½” that will fit the standard plastic C-5 aircrew checklist binders. Units may request copies of this checklist printed on a water proof-based media (in the size outlined) from the OPR. This product reduces weight and eliminates the need for plastic inserts. Limit water proof copies to aircrew only for use in-flight and training purposes.

PILOT SOLL II CHECKLIST INSERT

SOLL II After Landing	2
SOLL II Block-In	2
SOLL II Starting Engines.....	2
SOLL II Block-Out.....	3

Supersedes MCI 11-205V27, Annex A
OPR: HQ AMC/DOV (Maj Shepherd)
Certified by: HQ USAF/XOO (Maj Gen Michael S. Kudlacz)
Number of Printed Pages: 3 Distribution: F

SOLL II AFTER LANDING

- *1. Anti-Skid Switch - "OFF" (CP)
- *2. Pitot Heat and Angle of Attack De-Ice Switches – "OFF" (CP)
- *3. Cargo Doors Arming Switches – "AS REQUIRED" (CP)
- *4. IFF - "STATE SETTING" (CP)
- 5. Ram Air Turbine Switch - "RETRACT" (P)
- *6. Spoilers - "CLOSED" (CP)
- *7. Flaps and Slats - "STATE SETTING" (CP)
- *8. Radar - "AS REQUIRED" (P, N)

SOLL II BLOCK-IN

- *1. Brake Switch - "EMERGENCY" (CP)
- *2. Parking Brake - "SET" (P)
- *3. Landing Gear System Indicators - "CHECKED" (CP)
- *4. MLG Caster Switch - "CASTER" (P)
- 5. Continuous Ignition - "OFF" (P)
- 6. Fuel and Start Ignition - "STOP" (P)

SOLL II STARTING ENGINES

- 1. Clear to Start Engines - "ENGINES CLEAR TO START" (S), "STARTING NO. _____" (P)
- 2. Continuous Ignition - "ON" (P)
- 3. Flight Augmentation - "ON" (P)
- 4. ALDCS - "ON"(P)
- 5. Flaps and Slats - "STATE SETTING" (CP)

SOLL II BLOCK-OUT

1. MLG Caster Switch—"CENTER" (P)
2. Ram Air Turbine Switch—"AUTO" (P)
3. ADS Panel—"SAFE" (CP)
4. Door Open Lights—"OFF" (CP)
5. Brake Switch—"NORMAL" (CP)
6. Radar—"AS REQUIRED" (P, N)
7. AFCS—"OFF" (CP)
8. Crew Briefing—"COMPLETED" (P)
9. Command Markers—"SET" (CP, P)
10. Waypoint and TACAN Data—"LOADED" (CP, P, N)
11. Trim—"CHECKED AND SET" (CP)

MARVIN R. ESMOND, Lt General, USAF
DCS, Air and Space Operations